

HITACHI SELF-CONTAINED AIR CONDITIONERS

Models

- RUA-NP4ATS • RUA-NP5ATS
- RUA-NP6ATS • RUA-NP8ATS
- RUA-NP9ATS • RUA-NP10ATS
- RUA-NP13ATS • RUA-NP15ATS
- RUA-NP20ATS • RUA-NP25ATS
- RUA-NP30ATS



Nominal Cooling Capacity

12.2	kW	to	94.4	kW
10,500	kcal/h	to	81,200	kcal/h
41,600	Btu/h	to	322,100	Btu/h

All R410A RUA models are equipped with new design high efficient Hitachi scroll compressors for high ambient environment

1. Scroll portion is using asymmetric involute scroll, suction portion can increase 20% compression space, and reduce heat loss to have better efficiency.
2. Oil supply is using Trochoid pump supplying oil volume stably to ensure fully lubrication and improve reliability.
3. Two roller bearings (Main/Sub) design is increasing the strength of bearing, and stabilize operation to reduce mechanical loss.
4. Improving the route of refrigerant to lower compressor motor coil temperature.

All inclusive protection functions, higher reliability, longer duration

Equipped with 3 phases overcurrent transformer, high/low pressure switch, and compressor internal thermostat to improve compressor reliability greatly under tough environment.

New R410A RUA model features

New design step fin heat exchanger

New Ø7 tubes, Step Fin and multi route design high efficient heat exchanger to have better performance.



New development PCB control to fully improve unit protection and performance

1. Multi-compressors starting sequence can be controlled automatically to avoid particular compressor starting frequently and extend compressor duration.
2. Each protection devices can be detected independently, when abnormal condition occurs, the alarm code will be displayed.
3. PCB memory is able to save 5 failure resumes that can be retrieved to help inspection and service.

Using galvanized steel base

Improving unit structure strength and also to reduce unit damage risk during transportation and warehouse.

More optional functions and accessories can meet various demands

Optional functions items :

Air filter, Filter box, Strainer & Dryer, Sight glass, Anti-corrosion fin, Double layers insulator for indoor service cover, Condenser protected net, Soft starter for indoor motor.

More environment friendly

Using R410A refrigerant and reducing usage of woods in order to lower the impact of environment.

FEATURES

EFFICIENT, RELIABLE AND DURABLE NEW SERIES

Baked Paint Galvanized Steel Panels

Corrosion Resistant Cabinet

The weather proof characteristics of the panels have been significantly reinforced by the adoption of galvanized steel panel which have been coated with synthetic resin paint through our unique baking process. The resistant panels ensure long-lasting fine appearance, and maintenance work has been minimized.

Reliable Protection System

Compressor Protection

Each compressor is protected with the following components: reverse phase protection, overcurrent protector, internal thermostat, high pressure switch, low pressure switch and delay timer. This wide variety of protection devices provides perfect compressor guarding functions, assuring fewer service calls from customers.

Fan Motor

The evaporator fan motor is protected with thermal overcurrent relay and the condenser fan motors are protected with an internal thermostat.

Energy-Saving Design

Highly-Efficient Compressor

Low power input is achieved by specially developed compressors and heat exchanger and their suitable combinations.

Condenser

The adoption of a highly efficient step fin heat exchanger provides low operation cost.

Evaporator

Highly efficient step fin coils and inner grooved tube have been applied, to provide a large cooling capacity with low noise.

Insulated Indoor Compartment

This insulation compartment effectively eliminates heat loss.

Capacity Control (Dual or Multi Circuit Units)

Each unit is equipped with two, three or four compressors and two, three or four independent refrigeration cycle, so that one compressor operation can reduce the operation cost against a half load of one large compressor.

EFFECTIVELY MATCHED SELECTION FOR INDIVIDUAL APPLICATIONS

Optimum Matched Choice

High Temperature Operation

Designed for high outdoor temperatures, these units guarantee reliable operation even under condition up to an ambient temperature of 52°C(125°F).

Attractive Fan Performance

Adequate external static pressure by the evaporator fan can be obtained for individual ducting applications.

Minimum Installation Arrangement

Easy Installation

This easy-to-install and ready-to-operate unit ensure rapid and low cost installation work.

Pre-Drilled Duct Flange

Flanges are prepared at the supply and return duct connections so that they can reduce duct connection work at the site.

Factory-Completed

Only system connection work is required, excluding the installation work for auxiliary equipment.

Quiet Operation

Compressor

Noise and vibration have been effectively reduced by the adoption of new hermetic compressor.

Condenser Fan

This direct driven propeller fan is dynamically balanced to ensure smooth airflow.

Evaporator Fan

The centrifugal fan and fan casing are optimum shaped for efficient and low noise operation.

Reduced Maintenance Work


Easy Maintenance

Large service spaces and rapidly removable service panels have been provided for easy maintenance work.




UNIT DIMENSIONS




RUA-NP4ATS and RUA-NP5ATS






Mark	Name of Parts
1	Supply Air Connection
2	Return Air Connection
3	Condenser Air Intake (Both Sides)
4	Condenser Air Discharge
5	Indoor Side Condensate Drain Connection (FPT 3/4)
6	Service Panel for Magnetic Switch Box and Compressor
7	Service Panel for Indoor Fan Motor
8	Knockout Hole for Power Supply Wiring (ø26)
9	Knockout Hole for Operation Circuit Wiring (ø20)
10	Mounting Hole (4-ø12.5)
11	Lifting Hole (ø-ø50)




RUA-NP6ATS and RUA-NP8ATS






Mark	Name of Parts
1	Supply Air Connection
2	Return Air Connection
3	Condenser Air Intake (Both Sides)
4	Condenser Air Discharge
5	Indoor Side Condensate Drain Connection (FPT 3/4)
6	Service Panel for Magnetic Switch Box and Compressor
7	Service Panel for Indoor Fan Motor
8	Knockout Hole for Power Supply Wiring (ø26)
9	Knockout Hole for Operation Circuit Wiring (ø20)
10	Mounting Hole (4-ø12.5)
11	Lifting Hole (16-ø50)



RUA-NP9ATS and RUA-NP10ATS





Mark	Name of Parts
1	Supply Air Connection
2	Return Air Connection
3	Condenser Air Intake (Both Sides)
4	Condenser Air Discharge
5	Indoor Side Condensate Drain Connection (FPT 3/4)
6	Service Panel for Magnetic Switch Box and Compressor
7	Service Panel for Indoor Fan Motor
8	Knockout Hole for Power Supply Wiring (ø26)
9	Knockout Hole for Operation Circuit Wiring (ø20)
10	Mounting Hole (4-ø12.5)
11	Lifting Hole (16-ø50)



UNIT DIMENSIONS





RUA-NP13ATS and RUA-NP15ATS



Mark	Name of Parts
1	Supply Air Connection
2	Return Air Connection
3	Condenser Air Intake (Both Sides)
4	Condenser Air Discharge
5	Indoor Side Condensate Drain Connection (FPT 3/4 Both Sides)
6	Service Panel for Magnetic Switch Box and Compressor
7	Service Panel for Indoor Fan Motor
8	Knockout Hole for Power Supply Wiring (ø52)
9	Knockout Hole for Operation Circuit Wiring (ø20)
10	Mounting Hole (16-ø50)
11	Lifting Hole (16-ø50)



RUA-NP20ATS




Mark	Name of Parts
1	Supply Air Connection
2	Return Air Connection
3	Condenser Air Intake (Both Sides)
4	Condenser Air Discharge
5	Indoor Side Condensate Drain Connection (FPT 1)
6	Service Panel for Magnetic Switch Box and Compressor
7	Service Panel for Indoor Fan Motor
8	Knockout Hole for Power Supply Wiring (ø52)
9	Knockout Hole for Operation Circuit Wiring (ø20)
10	Mounting Hole


UNIT DIMENSIONS




RUA-NP25ATS




Mark	Name of Parts
1	Supply Air Connection
2	Return Air Connection
3	Condenser Air Intake (Both Sides)
4	Condenser Air Discharge
5	Indoor Side Condensate Drain Connection (PT1)
6	Service Panel for Magnetic Switch Box and Compressor
7	Service Panel for Indoor Fan Motor
8	Knockout Hole for Power Supply Wiring (ø52)
9	Knockout Hole for Operation Circuit Wiring (ø20)
10	Mounting Hole



RUA-NP30ATS



Mark	Name of Parts
1	Supply Air Connection
2	Return Air Connection
3	Condenser Air Intake (Both Sides)
4	Condenser Air Discharge
5	Indoor Side Condensate Drain Connection (PT1)
6	Service Panel for Magnetic Switch Box and Compressor
7	Service Panel for Indoor Fan Motor
8	Knockout Hole for Power Supply Wiring (ø52)
9	Knockout Hole for Operation Circuit Wiring (ø20)
10	Mounting Hole



UNIT GENERAL DATA

Models		RUA-NP4ATS	RUA-NP5ATS	RUA-NP6ATS	RUA-NP8ATS	RUA-NP9ATS	RUA-NP10ATS
Nominal Cooling Capacity at 35°C outdoor temperature*	kW	12.2	15.2	18.0	23.0	27.4	30.6
	kcal/h	10,500	13,100	15,500	19,800	23,600	26,300
	Btu/h	41,600	51,900	61,400	78,500	93,500	104,400
Nominal Cooling Capacity at 46°C outdoor temperature**	kW	10.5	13.0	15.8	20.0	23.2	25.9
	kcal/h	9,000	11,200	13,600	17,200	19,900	22,300
	Btu/h	35,500	44,400	53,900	68,200	79,200	88,400
Nominal Cooling Capacity at 48°C outdoor temperature***	kW	10.4	12.9	15.7	20.0	22.8	25.7
	kcal/h	8,900	11,100	13,500	17,200	19,600	22,100
	Btu/h	35,500	44,000	53,600	68,200	77,800	87,700
Capacity Control	%	100,0	100,0	100,0	100,0	100,55,0	100,50,0
Cabinet Color (MUNSELL CODE)	Synthetic Resin Paint Baked on Galvanized Steel Plates Beige (2.5Y 8/2)						
Outer Dimensions	Height	mm (in.)	1,070 (42-1/8)	1,070 (42-1/8)	1,070 (42-1/8)	1,070 (42-1/8)	1,070 (42-1/8)
	Width	mm (in.)	1,020 (40-3/16)	1,020 (40-3/16)	1,360 (53-17/32)	1,360 (53-17/32)	1,425 (56-3/32)
	Depth	mm (in.)	1,440 (56-11/16)	1,440 (56-11/16)	1,715 (67-17/32)	1,715 (67-17/32)	2,105 (82-7/8)
Net Weight	kg (lbs.)	230 (507)	230 (507)	310 (683)	330 (728)	410 (904)	420 (926)
Refrigerant	R410A					R410A	
Flow Control	Capillary Tube					Capillary Tube	
Number of Circuits	1					2	
Compressor	Hermetic Scroll						
Model	kW (hp)	E406DH	E506DH	E626DH	E856DH	E506DH/E406DH	E506DH
Motor		3.0 (4)	3.75 (5)	4.5 (6)	6.4 (8.5)	3.75/3.0 (5)/(4)	3.75 (5)
Quantity		1	1	1	1	1/1	2
Condenser	Multi-Pass Cross-Finned Tube						
Fan	Direct Driven Propeller Fan						
Air Flow	m³/min	132	132	150	150	175	175
Motor		kW (hp)	0.3 (2/5)	0.3 (2/5)	0.3 (2/5)	0.3 (2/5)	0.3 (2/5)
Quantity		1	1	1	1	1	1
Evaporator	Multi-Pass Cross-Finned Tube						
Fan	Multi-Blade Centrifugal Fan (Double Suction)						
Nominal Air Flow	m³/min m³/s	37	46	65	69	82	90
		0.62	0.77	1.08	1.15	1.37	1.5
Motor		L/s kW (hp)	620 0.55 (3/4)	770 0.55 (3/4)	1,080 0.75 (1)	1,150 0.75 (1)	1,370 1.5 (2)
Quantity	1						
Connections	Female Piping Thread Screw						
Condensate Drain	FPT	3/4	3/4	3/4	3/4	3/4	3/4
Size		1	1	1	1	1	1
Quantity	1						
Wiring Hole	Knockout Hole						
Main	mm (in.)	Φ26 (1-1/32)	Φ26 (1-1/32)	Φ52 (2-1/16)	Φ52 (2-1/16)	Φ52 (2-1/16)	Φ52 (2-1/16)
Control		mm (in.)	Φ20 (25/32)	Φ20 (25/32)	Φ20 (25/32)	Φ20 (25/32)	Φ20 (25/32)
Shipping Weight	kg (lbs.)	240	240	320	340	430	440
		1	1	1	1	1	1
Approximate	Height Width Depth	mm (in.)	1,115 (43-29/32)	1,115 (43-29/32)	1,115 (43-29/32)	1,115 (43-29/32)	1,115 (43-29/32)
Packing List		mm (in.)	1,070 (42-1/8)	1,070 (42-1/8)	1,410 (55-1/2)	1,410 (55-1/2)	1,475 (58-1/16)
		mm (in.)	1,500 (59-1/16)	1,500 (59-1/16)	1,775 (69-7/8)	1,775 (69-7/8)	2,165 (85-1/4)
Measurements	m³	1.79	1.79	2.79	2.79	3.56	3.56

Notes :

1. The capacities are gross capacities, which include the effect of evaporator fan motor heat.
2. The nominal cooling capacity is according to JIS B8616-2006, and based on the following condition.

Evaporator Air Inlet Temperature

*27°C DB/19°C WB (80°F DB/66°F WB)

**29°C DB/19°C WB (84°F DB/66°F WB)

***26.6°C DB/19.4°C WB (80°F DB/67°F WB)

Condenser Air Inlet Temperature

35°C DB (95°F DB)

46°C DB (115°F DB)

48°C DB (118°F DB)

Evaporator Air Flow

Nominal Air Flow

Nominal Air Flow

Max. Air Flow

UNIT GENERAL DATA

Models		RUA-NP13ATS	RUA-NP15ATS	RUA-NP20ATS	RUA-NP25ATS	RUA-NP30ATS	
Nominal Cooling Capacity at 35°C outdoor temperature*	kW kcal/h Btu/h	36.4 31,300 124,200	46.8 40,200 159,700	61.3 52,700 209,200	73.8 63,500 251,800	94.4 81,200 322,100	
Nominal Cooling Capacity at 46°C outdoor temperature**	kW kcal/h Btu/h	32.7 28,100 111,600	42.1 36,200 143,600	53.2 45,700 181,500	65.3 56,100 222,800	84.2 72,400 287,300	
Nominal Cooling Capacity at 48°C outdoor temperature***	kW kcal/h Btu/h	32.4 27,900 110,500	41.5 35,700 141,600	52.4 45,100 178,800	65.1 56,000 222,100	83.2 71,500 283,900	
Capacity Control	%	100,60,0	100,50,0	100,62,0	100,66,0	100,50,0	
Cabinet Color (MUNSELL CODE)		Synthetic Resin Paint Baked on Galvanized Steel Plates Beige (2.5Y 8/2)					
Outer Dimensions	Height	mm (in.)	1,480 (58-9/32)	1,480 (58-9/32)	1,980 (77-15/16)	1,765 (69-1/2)	1,990 (78-11/32)
	Width	mm (in.)	1,600 (63)	1,600 (63)	1,900 (74-13/16)	1,900 (74-13/16)	2,000 (78-3/4)
	Depth	mm (in.)	1,965 (77-3/8)	1,965 (77-3/8)	2,450 (96-15/32)	3,000 (118-1/8)	3,000 (118-1/8)
Net Weight	kg (lbs.)	580 (1,278)	610 (1,344)	790 (1,740)	900 (1,982)	1,055 (2,324)	
Refrigerant		R410A		R410A		R410A	
Flow Control		Capillary Tube		Capillary Tube		Capillary Tube	
Number of Circuits		2		3		4	
Compressor		Hermetic Scroll					
Model		E856DH/E506DH	E856DH	E856DH/E506DH/E856DH	E856DH	E856DH	
Motor	kW (hp)	6.4/3.75 (8.5)/(5)	6.4 (8.5)	6.4/3.75/6.4 (8.5)/(5)/(8.5)	6.4 (8.5)	6.4 (8.5)	
Quantity		1/1	2	1/1/1	3	4	
Condenser		Multi-Pass Cross-Finned Tube					
Fan		Direct Driven Propeller Fan					
Air Flow	m³/min	280	300	375	530	700	
Motor	kW (hp)	0.3 (2/5)	0.3 (2/5)	0.3 (2/5)	0.3 (2/5)	0.3 (2/5)	
Quantity		2	2	2	3	4	
Evaporator		Multi-Pass Cross-Finned Tube					
Fan		Multi-Blade Centrifugal Fan (Double Suction)					
Nominal Air Flow	m³/min	110	130	175	234	260	
	m³/s	1.83	2.17	2.92	3.9	4.33	
Motor	L/s	1,830	2,170	2,920	3,900	4,330	
Quantity	kW (hp)	2.2 (3)	2.2 (3)	3.7 (5)	5.5 (7.5)	5.5 (7.5)	
Connections		Female Piping Thread Screw					
Condensate Drain		FPT					
Size		3/4	3/4	1	1	1	
Quantity		1	1	1	1	1	
Wiring Hole		Knockout Hole					
Main	mm (in.)	Φ 52 (2-1/16)	Φ 52 (2-1/16)	Φ 52 (2-1/16)	Φ 52 (2-1/16)	Φ 52 (2-1/16)	
Control	mm (in.)	Φ 20 (25/32)	Φ 20 (25/32)	Φ 20 (25/32)	Φ 20 (25/32)	Φ 20 (25/32)	
Shipping Weight	kg (lbs.)	610 (1,344)	640 (1,410)	960 (2,115)	1,085 (2,390)	1,250 (2,753)	
Approximate Packing List	Height	mm (in.)	1,525 (60-1/32)	1,525 (60-1/32)	2,110 (83-1/16)	1,945 (76-9/16)	2,170 (85-7/16)
	Width	mm (in.)	1,650 (64-31/32)	1,650 (64-31/32)	2,100 (82-11/16)	2,100 (82-11/16)	2,200 (86-5/8)
	Depth	mm (in.)	2,005 (78-15/16)	2,005 (78-15/16)	2,570 (101-3/16)	3,100 (122-1/16)	3,100 (122-1/16)
Measurements	m³	5.05	5.05	11.39	12.66	14.80	

Notes :

1. The capacities are gross capacities, which include the effect of evaporator fan motor heat.

2. The nominal cooling capacity is according to JIS B8616-2006, and based on the following condition.

Evaporator Air Inlet Temperature

*27°C DB/19°C WB (80°F DB/66°F WB)

**29°C DB/19°C WB (84°F DB/66°F WB)

***26.6°C DB/19.4°C WB (80°F DB/67°F WB)

Condenser Air Inlet Temperature

35°C DB (95°F DB)

46°C DB (115°F DB)

48°C DB (118°F DB)

Evaporator Air Flow

Nominal Air Flow

Nominal Air Flow

Max. Air Flow

Specifications in this catalog are subject to change without notice, in order that HITACHI may bring the latest innovations to our customers.